


Aksel LD

Load Capacity (lbs)
50-250*

Shelf Depth Range (in)
5-8**



About Aksel LD

Back bar is 1/4" thick, hot-rolled steel.

Rods are inset 2" on center (OC) from left and right bar end.

Request custom rods 1 1/2" shorter than shelf depth.

Supports up to 50 lbs. per solid rod when correctly mounted.*

Manufactured from top-quality American steel made with 70% recycled content.

Designed & engineered in the U.S. of Awesome.

Shelfology radically recycles all production metal, wood, and cardboard waste.

***WARNING:** All brackets must be installed into studs or posts. Failure to do so may result in saggy shelves, falling objects, or even injury.

**Request custom rod length for shelf depth applications below 5".

***Drawings are representations only and not to scale.

U.S. Patent No. 20240090667

© Shelfology 2025

Figure	Rod Ct	Style	Load	Back bar Ln	Rod Spc (OC)	Weight (lbs)	Shelf Ln	Rod Ln	Shelf Thickness
A	1	LD	50 lbs	1" (Square)	NA	0.4	NA	4 1/2", 6"	1/4"
B	1	LD	50 lbs	1" (Round)	NA	0.4	NA	4 1/2", 6"	1/4"
C	2	LD	100 lbs	10"	6"	1.2	12"-16"	4 1/2"	1/4"
C	2	LD	100 lbs	14"	10"	1.5	16"-20"	4 1/2"	1/4"
C	2	LD	100 lbs	18"	14"	1.8	20"-24"	4 1/2"	1/4"
C	2	LD	100 lbs	22"	18"	2.2	24"-28"	4 1/2"	1/4"
C	2	LD	100 lbs	26"	22"	2.5	28"-32"	4 1/2"	1/4"
C	2	LD	100 lbs	30"	26"	2.9	32"-36"	4 1/2"	1/4"
D	3	LD	150 lbs	34"	15"	3.5	36"-40"	4 1/2"	1/4"
D	3	LD	150 lbs	38"	17"	3.7	40"-44"	4 1/2"	1/4"
D	3	LD	150 lbs	42"	19"	4.0	44"-48"	4 1/2"	1/4"
D	3	LD	150 lbs	46"	21"	4.3	48"-52"	4 1/2"	1/4"
E	4	LD	200 lbs	50"	15 3/8"	4.9	52"-56"	4 1/2"	1/4"
E	4	LD	200 lbs	54"	16 3/8"	5.3	56"-60"	4 1/2"	1/4"
E	4	LD	200 lbs	58"	18"	5.8	60"-72"	4 1/2"	1/4"
F	5	LD	250 lbs	70"	16 1/2"	6.7	72"-80"	4 1/2"	1/4"
F	5	LD	250 lbs	78"	18 1/2"	7.4	80"-87"	4 1/2"	1/4"

