
## **Floaty**

Load Capacity (lbs)

20\*

Weight (lbs)

1.06



B

| 3/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" | -13/4" |

## About Floaty

Shelf milled from a single piece of solid hardwood.

Solid 14 gauge steel keyhole mounting plate is set at a 4½° angle, so that as more downforce is applied to the shelf surface, the shelf abuts tighter to the wall.

1" double-headed fastener screws are used for mounting to the wall.

Designed to be mounted into studs, blocking, or drywall anchors only.

Mounting guide template included with each shelf.

Holds up to 20 pounds per shelf.

Manufactured from top-quality American steel made with 70% recycled content.

Designed and produced in beautiful middleof-nowhere Idaho, with sweat, tears, and Ameri-quality awesomeness.

Shelfology radically recycles all production metal, wood and cardboard waste.

\*WARNING: Shelf hardware must be correctly installed into studs, wall blocking or wall anchors. Failure to do so may result in sagging shelves, falling objects, or serious injury.

\*\*\*Drawings are representations only and not to scale.

© Shelfology 2023





Figure	Orientation	Load (lbs)	Shelf Ln	Shelf Dp	Shelf Thickness	Weight (lbs)
A	Front	20	5"	5"	1¾"	1.06
B	Back	20	5"	5"	1¾"	1.06

