
## **Shingle Hook**


Weight (lbs)


1


Load Capacity (lbs)


150
































## Shingle Hook

Made from 1/8" thick hot-rolled steel.

Hardwood backplate option made from ¼" thick solid walnut, maple, or white oak.

Screw holes are set  $\frac{5}{16}$ " OC from top and bottom edge of plates.

Screw holes are  $\frac{3}{16}$ "outside diameter (OD).

Supports 150lbs per hook when correctly mounted.\*

Manufactured from top-quality American steel made with 70% recycled content.

Designed and produced in beautiful middle-of-nowhere Idaho, with sweat, tears, and Ameri-quality awesomeness.

Shelfology radically recycles all production metal, wood and cardboard waste.

\*WARNING: All hooks must be installed into studs, posts, or dry wall anchors. Failure to do so may result in saggy hooks, falling objects, or even injury.

\*\*Drawings are representations only and not to scale.

© Shelfology 2022





Figure	Hook Material	Backplate Material	Height	Width	Depth	Weight (lbs)	Load (lbs)
Α	Steel	Steel	4"	4"	17/8"	0.98	150
В	Steel	Steel	4"	4"	17/8"	1	150
С	Steel	Hardwood	4"	4"	2"	± 0.50	150
D	Steel	Hardwood	4"	4"	2"	± 0.52	150

